



Project Name: _____
Date: _____
Location: _____
Type: _____
Model Number: _____
Quantity: _____
Prepared By: _____
Comments: _____



Description

The Lumen Logic™ LogiWell Bunker Face Well Light is an in ground fixture that allows for use in places where the light itself should not be seen at all. It can be flush mounted in the dirt for a clean installation. This bunker version aims light outwards 360° from five openings which enables it to be used as a marker light on a pathway or trail. Comes with a lifetime warranty.

Specifications

Materials

Construction	Cast Brass
Finish	Bronze
Lead Wire	4' 16AWG
Lens	Flat Clear Glass
Mounting	Direct Installation

Photometrics

Light Source	LED 5 Watt MR16 Lamp
Light Output (Lumens)	20 Lumens
Beam Angle	38°
Color Temperature (CCT)	2700K
Color Rendering Index (CRI)	>80
Lamp Life (L70)	40,000 Hours

Electrical

Energy Consumption (watts)	5.0 Watts
Power Factor	0.61
Operating Voltage Range	12-15 Volts
Power Supply	Low Voltage Transformer

Installation

Orientation	Directed upwards only
-------------	-----------------------

Certifications

Certifications	UL & cUL listed
Warranty	Lifetime

Dimensions

Height	5.1"
Width	5.0"
Depth	5.0"

Notes

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.