



Project Name: \_\_\_\_\_  
Date: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Model Number: \_\_\_\_\_  
Quantity: \_\_\_\_\_  
Prepared By: \_\_\_\_\_  
Comments: \_\_\_\_\_



### Description

The Lumen Logic™ LogiWell Open face well light is an in ground fixture that allows for use in places where the light itself should not be seen at all. It can be flush mounted in the dirt for a clean and hidden installation. Comes with a lifetime warranty.

### Specifications

#### Materials

Construction	Cast Brass
Finish	Bronze
Lead Wire	4' 16AWG
Lens	Flat Clear Glass
Mounting	Direct Installation

#### Photometrics

Light Source	LED 5 Watt MR16 Lamp
Light Output (Lumens)	340 Lumens
Beam Angle	38°
Color Temperature (CCT)	2700K
Color Rendering Index (CRI)	>80
Lamp Life (L70)	40,000 Hours

#### Electrical

Energy Consumption (watts)	5.0 Watts
Power Factor	0.61
Operating Voltage Range	12-15 Volts
Power Supply	Low Voltage Transformer

#### Installation

Orientation	Directed upwards only
-------------	-----------------------

#### Certifications

Certifications	UL & cUL listed
Warranty	Lifetime

### Dimensions

Height	4.5"
Width	5.0"
Depth	5.0"

#### Notes

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.  
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.