

## INSTALLATION & MAINTENANCE GUIDE

**AMP<sup>®</sup>** Lighting

AMP<sup>®</sup> Low Voltage Landscape Lighting

AMP<sup>®</sup> Estate PendantPro Hanging Light

ASI-9006-4036-B-BZ

**Help Hotline:**

1-813-978-3900 • Mon-Fri 9am-6pm (EST)

[www.amplighting.com](http://www.amplighting.com)



AMP® Estate PendantPro Hanging Light  
ASI-9006-4036-B-BZ



## Important Safety Instructions: Read Before Installation

This fixture is intended for installation in accordance with local codes and the National Electric Code (NEC). Failure to adhere to these codes and instructions may result in serious injury, property damage and void the warranty.

These instructions do not intend to cover all variations in installation, operation maintenance or mounting situations.

1. Make sure that the power is turned OFF before installing or servicing this luminaire.
2. **WARNING:** risk of electrical shock. Install all luminaires 10 feet (3.05M) or more from pool, spa or fountain.
3. This luminaire is intended to be used only with a power supply (transformer) rated maximum of 300 watts (25 AMPS) at 15 volts.
4. Wiring connections must be made with UL listed wire connectors that are suitable for outdoor use.
5. The unit low voltage cable should:
  - a. Be protected by routing in close proximity to the luminaire or fitting, or next to a building structure such as a house or deck;
  - a. Not be buried except for a maximum 6 inches (15.2 cm) in order to connect to the main low voltage cable; and
  - a. Have the length cut off so that it is connected to a connector within 6 inches (15.2 cm) from the building structure, a luminaire, or fitting.



## Important Safety Instructions

INSTRUCTIONS PERTAINING TO A RISK OF FIRE, OR INJURY TO PERSONS  
**Lighted lamp is HOT!**

**WARNING - TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS.**

1. Turn off/unplug and allow to cool before reducing lamp.
2. Lamp gets **HOT** quickly! Contact only switch/plug when turning on.
3. Do not touch the hot lens, guard or enclosure.
4. Keep lamp away from materials that may burn.
5. Do not touch lamp at any time. Use a soft cloth. Oil from skin may damage lamp.
6. Do not operate the luminaire fitting with a missing or damaged shield.

SAVE THESE INSTRUCTIONS


## Package Contents

- |                      |                            |
|----------------------|----------------------------|
| A. (1) Fixture       | D. (1) Mounting Bracket    |
| B. (1) Fixture Chain | E. (3) Self-tapping Screws |
| C. (1) Chain Link    | F. (3) Flat Washers        |

## Parts Required (Sold Separately)


- A. (1) LED MR16 Lamp or (1) Bi-Pin  
Brass Puck Light

## Product Dimensions





## 1 Remove Shade




Remove the top of the shade from the bottom of the shade to expose the socket.

Two kinds of bulbs are suitable for this fixture.

1. MR16 Bulb: Option 1
2. Bi-Pin Brass Puck Light: Option 2

### Option 1: MR16 Bulb

## 1 Install MR16 Bulb



Insert the MR16 bulb with the correct wattage and type marked on the fixture label.

**CAUTION:** This fixture is for LED use only. Do not exceed maximum wattage marked on luminaire label.

**NOTE:** DO NOT touch MR16 bulb with bare hands. Use soft cloth to handle MR16 bulb.


Go to Step 3 to complete installation.

# AMP® AMP® Estate PendantPro Hanging Light ASI-9006-4036-B-BZ


## Option 2: Bi-Pin Puck Light

### 1 Remove Clips

Remove the clip from the socket by removing the screws.



### 2 Install Bi-Pin Brass Puck Light



Insert the Bi-pin brass puck light into the socket and secure it in place with the two screws previously removed from the clip.


**CAUTION:** This fixture is for LED use only. Do not exceed maximum wattage marked on luminaire label.

**NOTE:** DO NOT touch the Bi-pin brass puck light with bare hands. Use soft cloth to handle the puck light.

Go to Step 3 to complete installation.




**3** Install Shade



Thread the top of the shade back onto the bottom of the shade.


**4** Install Mounting Bracket



Attach the mounting bracket onto the desired ceiling surface. Secure with the flat washers and self-tapping screws.

Note: Wall anchors are required for certain installation conditions (concrete or brick walls). Mark on the desired ceiling surface for wall anchors by using the holes on the mounting bracket. Remove the mounting bracket and drill proper holes on the desired ceiling surface and then insert the wall anchors.

## 5 Attach Fixture to Mounting Bracket




Adjust the fixture chain to the desired length by removing the links if needed. (Note: Pliers are required for this step).

With the fixture chain unattached to the fixture loop on top of the fixture body; or the ceiling loop on the underside of the mounting bracket, pull the supply wires through the fixture chain alternating between the links.

After the wires are through the fixture chain, pull the supply wires up and around the backside of the mounting bracket.

Attach one end of the fixture chain to the fixture loop at the top of the fixture body. Lift the fixture body and fixture chain up and attach the other end of the fixture chain onto the ceiling loop on the bottom of the mounting bracket with the chain link.

The fixture will now hang safely. Close the chain loop at the ceiling loop.



Strip both leads from the luminaire pigtail. Connect the leads from the luminaire supply cable to the transformer (sold separately).